



**SECTION I – IDENTIFICATION**

<b>PRODUCT IDENTIFIER</b> Feldspathic Sand - Unrefined	<b>TRADE NAME</b> Feldspathic Sand - Unrefined	<b>OTHER SYNONYMS</b> Granular Feldspar
<b>RECOMMENDED USE AND RESTRICTION ON USE</b> Used in industrial manufacturing This product is not intended or designed for and should not be used as an abrasive blasting medium or for foundry applications.		
<b>MANUFACTURER/SUPPLIER INFORMATION</b> Martin Marietta Materials 4123 Parklake Ave Raleigh, North Carolina 27612 Phone: 919-781-4550  For additional health, safety or regulatory information and other emergency situations, call 919-781-4550		

**SECTION II – HAZARD(S) IDENTIFICATION**

<p><b>HAZARD CLASSIFICATION:</b>            Category 1A Carcinogen            Category 1 Specific Target Organ Toxicity (STOT) following repeated exposures            Category 2A Eye Irritant            Category 2 Skin Irritant</p> <p><b>SIGNAL WORD: DANGER</b></p> <p><b>HAZARD STATEMENTS:</b>            May cause cancer by inhalation.            Causes damage to lungs, kidneys and autoimmune system through prolonged or repeated exposure by inhalation.            Causes skin irritation and serious eye irritation.</p> <p><b>PRECAUTIONARY STATEMENTS</b>            Do not handle until the safety information presented in this SDS has been read and understood.            Do not breathe dusts or mists. Do not eat, drink or smoke while manually handling this product. Wash skin thoroughly after manually handling.            If swallowed: If gastrointestinal discomfort occurs and if person is conscious, give a large quantity of water and induce vomiting; however, never attempt to make an unconscious person drink or vomit.            If on skin (or hair): Rinse skin after manually handling and wash contaminated clothing if there is potential for direct skin contact before reuse.            If inhaled excessively: Remove person to fresh air and keep comfortable for breathing.            If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, and continue rinsing.            If exposed, concerned, unwell or irritation of the eyes, skin, mouth or throat/nasal passage persist: Get medical attention.            Wear eye protection and respiratory protection following this SDS, NIOSH guidelines and other applicable regulations. Use protective gloves if manually handling the product.</p> <p>Avoid creating dust when handling, using or storing. Use with adequate ventilation to keep exposure below recommended exposure limits.</p> <p>Dispose of product in accordance with local, regional, national or international regulations.</p> <p>Please refer to Section XI for details of specific health effects of the components.</p>	 
---	---

**SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS**

COMPONENT(S) CHEMICAL NAME	CAS REGISTRY NO	% by weight (approx)
Feldspar	68476-25-5	40-60
Quartz (Silicon Dioxide - Crystalline)	14808-60-7	30-40
Mica	12001-26-2	0-6
Water	7732-18-5	5-15

**SECTION IV – FIRST-AID MEASURES**

**INHALATION:** If excessive inhalation occurs, remove to fresh air. Dust in throat and nasal passages should clear spontaneously. Contact a physician if irritation persists or develops later.

**EYES:** Immediately flush eye(s) with plenty of clean water for at least 15 minutes, while holding the eyelid(s) open. Occasionally lift the eyelid(s) to ensure thorough rinsing. Remove contact lenses, if present and easy to do, and continue rinsing. Beyond flushing, do not attempt to remove material from the eye(s). Contact a physician if irritation persists or develops later.

**SKIN:** Rinse skin with soap and water after manually handling and wash contaminated clothing if there is potential for direct skin contact. Contact a physician if irritation persists or develops later.

**INGESTION:** If gastrointestinal discomfort occurs and if person is conscious, give a large quantity of water and induce vomiting; however, never attempt to make an unconscious person drink or vomit. Get medical attention.

**SIGNS AND SYMPTOMS OF EXPOSURE:** There are generally no signs or symptoms of exposure to respirable crystalline silica. Often, chronic silicosis has no symptoms. The symptoms of chronic silicosis, if present, are shortness of breath, wheezing, cough and sputum production. The symptoms of acute silicosis which can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as 6 months, are the same as those associated with chronic silicosis; additionally, weight loss and fever may also occur. The symptoms of scleroderma, an autoimmune disease, include thickening and stiffness of the skin, particularly in the fingers, shortness of breath, difficulty swallowing and joint problems.

Direct skin and eye contact with dust may cause irritation by mechanical abrasion. Some components of the product are also known to cause irritant effects to skin, eyes and mucous membranes. Ingestion of large amounts may cause gastrointestinal irritation and blockage. Inhalation of dust may irritate nose, throat, mucous membranes and respiratory tract by mechanical abrasion. Coughing, sneezing, chest pain, shortness of breath, inflammation of mucous membrane, and flu-like fever may occur following exposures in excess of appropriate exposure limits. Repeated excessive exposure may cause pneumoconiosis, such as silicosis and other respiratory effects.

**SECTION V – FIRE-FIGHTING MEASURES****EXTINGUISHING AGENT**

Not flammable; use extinguishing media compatible with surrounding fire.

**UNUSUAL FIRE AND EXPLOSION HAZARD**

Contact with powerful oxidizing agents may cause fire and/or explosions (see Section X of this SDS).

**SPECIAL FIRE FIGHTING PROCEDURES**

None known

**HAZARDOUS COMBUSTION PRODUCTS**

None known

**SECTION VI – ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Persons involved in cleaning should first follow the precautions defined in Section VII of the SDS. Spilled materials, where dust can be generated, may overexpose cleanup personnel to respirable crystalline silica-containing dust and other components that may pose inhalation hazards. Do not dry sweep spilled material. Collect the material using a method that does not produce dust such as a High-Efficiency Particulate Air (HEPA) vacuum or thoroughly wetting down the dust before cleaning up. Wear appropriate personal protective equipment as specified in Section VIII including appropriate respirators during and following clean up or whenever airborne dust is present to ensure worker exposures remain below occupational exposure limits (OELs - Refer to Section VIII).

Place the dust in a covered container appropriate for disposal. Dispose of the dust according to federal, state and local regulations.

This product is not subject to the reporting requirements of SARA Title III Section 313, and 40 CFR 372.

**SECTION VII – HANDLING AND STORAGE**

This product is not intended or designed for and should not be used as an abrasive blasting medium or for foundry applications. Follow protective controls set forth in Section VIII of this SDS when handling this product. Dust containing respirable crystalline silica and other components that may be irritants may be generated during processing, handling and storage. Use good housekeeping procedures to prevent the accumulation of dust in the workplace.

Do not breathe dust. Avoid contact with skin and eyes. Do not store near food or beverages or smoking materials. Do not stand on piles of materials; it may be unstable.

Use adequate ventilation and dust collection equipment and ensure that the dust collection system is adequate to reduce airborne dust levels to below the appropriate OELs. If the airborne dust levels are above the appropriate OELs, use respiratory protection during the establishment of engineering controls. Refer to Section VIII - Exposure Controls/Personal Protection for further information.

In accordance with OSHA's Hazard Communication Standard (29 CFR 1910.1200, 1915.99, 1917.28, 1918.90, 1926.59, 1928.21), state, and/or local right-to-know laws and regulations, familiarize your employees with this SDS and the information contained herein. Warn your employees, your customers and other third parties (in case of resale or distribution to others) of the potential health risks associated with the use of this product and train them in the appropriate use of personal protective equipment and engineering controls, which will reduce their risks of exposure.

See also ASTM International standard practice E 1132-06, "Standard Practice for Health Requirements Relating to Occupational Exposure to Respirable Crystalline Silica."

For safe handling and use of this product for Hydraulic Fracturing, please see the OSHA/NIOSH Hazard Alert Worker Exposure to Silica during Hydraulic Fracturing DHHS (NIOSH) Publication No. 2012-166 (2012).

[http://www.osha.gov/dts/hazardalerts/hydraulic\\_frac\\_hazard\\_alert.pdf](http://www.osha.gov/dts/hazardalerts/hydraulic_frac_hazard_alert.pdf)

**SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION****Airborne OELs for Components of Feldspathic Sand - Unrefined:**

COMPONENT(S) CHEMICAL NAME	MSHA/OSHA PEL	ACGIH TLV-TWA	NIOSH REL
Feldspar	-	-	-
Quartz (Silicon Dioxide - Crystalline) <sup>§</sup>	(R) 0.05 mg/m <sup>3</sup> (R) 0.025 mg/m <sup>3</sup> (AL)	(R) 0.025 mg/m <sup>3</sup> #	(R) 0.05 mg/m <sup>3</sup> #
Mica	20 mppcf <sup>**</sup>	(R) 3 mg/m <sup>3</sup>	(R) <sup>##</sup> 3 mg/m <sup>3</sup>

<sup>§</sup> The OSHA OELs for respirable crystalline silica are listed in the table. As of June 28, 2018, the MSHA standard for respirable crystalline silica has not been changed but may be revised in the future. The MSHA PEL for dust containing crystalline silica (quartz) is based on the silica content of the respirable dust sample and is calculated as: 10 mg/m<sup>3</sup>/(% SiO<sub>2</sub>+2). The MSHA PEL for crystalline silica as tridymite and cristobalite is one-half the PEL for crystalline silica (quartz).

# The ACGIH and NIOSH limits are for crystalline silica (quartz), independent of the dust concentration. The ACGIH TLV for crystalline silica as cristobalite is equal to the TLV for crystalline silica as quartz. In 2005, ACGIH withdrew the TLV for crystalline silica as tridymite. The NIOSH REL for crystalline silica as cristobalite and tridymite is the same as for quartz. Refer to Section X for thermal stability information for crystalline silica (quartz).

AL: Action Level

\*\* : Millions of particles per cubic foot of air, using impinger sampling techniques per OSHA's Annotated Table Z-3 for Mineral Dusts.

##: Limit for mica containing less than 1% quartz

(R): Respirable Fraction.

**Airborne OELs for Inert/Nuisance Dust:**

Standard	Respirable Dust	Total Dust
MSHA/OSHA PEL (as Inert or Nuisance Dust)	5 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>
ACGIH TLV (as Particles Not Otherwise Specified)	3 mg/m <sup>3</sup>	*10 mg/m <sup>3</sup>
NIOSH REL (Particulates Not Otherwise Regulated)	-	-

Note: The limits for Inert Dust are provided as guidelines. Nuisance dust is limited to particulates not known to cause systemic injury or illness.

\* The TLV provided is for inhalable particles not otherwise specified.

**ENGINEERING CONTROLS**

Ventilation: Use local exhaust, general ventilation or natural ventilation adequate to maintain exposures below appropriate exposure limits.

Other control measures: Respirable dust and crystalline silica levels should be monitored regularly. Dust and crystalline silica levels in excess of appropriate exposure limits should be reduced by implementing feasible engineering controls, including (but not limited to) dust suppression (wetting), ventilation, process enclosure and enclosed employee work stations.

**EYE/FACE PROTECTION**

Safety glasses with side shields should be worn as minimum protection. Dust goggles should be worn when excessively (visible) dusty conditions are present or are anticipated. If irritation persists, get medical attention immediately. There is potential for severe eye irritation if exposed to excessive concentrations of dust for those using contact lenses.

**SKIN PROTECTION**

Use appropriate protective gloves if manually handling the product.

**RESPIRATORY PROTECTION**

Respirator Recommendations:

For respirable crystalline silica levels that exceed or are likely to exceed appropriate exposure limits, a NIOSH-approved particulate filter respirator must be worn. Respirator use must comply with applicable MSHA or OSHA standards, which include provisions for a user training program, respirator repair and cleaning, respirator fit testing, and other requirements. For additional information contact NIOSH at 1-800-356-4674 or visit website: <http://www.cdc.gov/niosh/npg> (search for crystalline silica). See also ANSI standard Z88.2 (latest revision) "American National Standard for Respiratory Protection," 29 CFR 1910.134 and 1926.103, and 42 CFR 84.

**SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION, CONTD.**

NIOSH recommendations for respiratory protection for crystalline silica include:

**Up to 0.5 mg/m<sup>3</sup>:**

(APF = 10) Any particulate respirator equipped with an N95, R95, or P95 filter (including N95, R95, and P95 filtering facepieces) except quarter-mask respirators. The following filters may also be used: N99, R99, P99, N100, R100, P100.

**Up to 1.25 mg/m<sup>3</sup>:**

(APF = 25) Any powered, air-purifying respirator with a high-efficiency particulate (100-series) filter.

(APF = 25) Any supplied-air respirator operated in a continuous-flow mode

**Up to 2.5 mg/m<sup>3</sup>:**

(APF = 50) Any air-purifying, full-facepiece respirator with an N100, R100, or P100 filter.

(APF = 50) Any powered, air-purifying respirator with a tight-fitting facepiece and a high-efficiency particulate filter

**Up to 25 mg/m<sup>3</sup>:**

(APF = 1000) Any supplied-air respirator operated in a pressure-demand or other positive-pressure mode

Emergency or planned entry into unknown concentrations or IDLH conditions (50 mg/m<sup>3</sup> for crystalline silica-quartz): A self-contained breathing apparatus (SCBA) that has a full-face piece and is operated in a pressure-demand or other positive-pressure mode or any supplied-air respirator that has a full-face piece and is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained positive-pressure breathing apparatus.

Escape from unknown or IDLH conditions: An air-purifying, full-face piece respirator with a high-efficiency particulate (100-series) filter or any appropriate escape-type, self-contained breathing apparatus.

If the workplace airborne crystalline silica concentration is unknown for a given task, conduct air monitoring to determine the appropriate level of respiratory protection to be worn. Consult with a certified industrial hygienist, your insurance risk manager or the OSHA Consultative Services group for detailed information. Ensure appropriate respirators are worn, as needed, during and following the task, including clean up or whenever airborne dust is present, to ensure worker exposures remain below OELs.

**GENERAL HYGIENE CONSIDERATIONS**

There are no known hazards associated with this material when used as recommended. Following the guidelines in this SDS are recognized as good industrial hygiene practices. Avoid breathing dust. Avoid skin and eye contact. Wash dust-exposed skin with soap and water before eating, drinking, smoking and using toilet facilities. Wash work clothes after each use.

**SECTION IX— PHYSICAL AND CHEMICAL PROPERTIES**

<b>APPEARANCE</b> The product is white in color and has the texture and appearance of sand.	<b>ODOR AND ODOR THRESHOLD</b> Odorless and not applicable
<b>pH AND VISCOSITY</b> Not applicable	<b>MELTING POINT/FREEZING POINT</b> 1238°C (2260°F) and not applicable
<b>BOILING POINT AND RANGE</b> 2230 °C (4046 °F)	<b>FLASH POINT AND FLAMMABILITY</b> Not applicable
<b>FLAMMABILITY/EXPLOSIVE LIMITS AND AUTOIGNITION TEMPERATURE</b> Not applicable	<b>EVAPORATION RATE AND DECOMPOSITION TEMPERATURE</b> Not applicable
<b>VAPOR PRESSURE AND VAPOR DENSITY IN AIR</b> Not applicable	<b>SPECIFIC GRAVITY.</b> 3.0
<b>SOLUBILITY IN WATER</b> Insoluble	<b>PARTITION COEFFICIENT: N-OCTANOL/WATER</b> Not applicable

**SECTION X – STABILITY AND REACTIVITY****STABILITY**

Stable

**CONDITIONS TO AVOID**

Contact with incompatible materials (see below).

**THERMAL STABILITY**

If crystalline silica (quartz) is heated to more than 870°C (1598°F), it can change to a form of crystalline silica known as tridymite, and if crystalline silica (quartz) is heated to more than 1470°C (2678°F), it can change to a form of crystalline silica known as cristobalite.

**INCOMPATIBILITY (Materials to avoid)**

Contact with powerful oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride may cause fire and/or explosions.

**HAZARDOUS DECOMPOSITION PRODUCTS**


Silica dissolves in hydrofluoric acid producing a corrosive gas - silicon tetrafluoride.

**HAZARDOUS POLYMERIZATION**

Not known to polymerize

**SECTION XI – TOXICOLOGICAL INFORMATION**

Health Effects: The information below represents an overview of health effects caused by overexposure to one or more components in Feldspathic Sand - Unrefined.

Primary routes(s) of exposure:      ■ Inhalation       Skin      ■ Ingestion

**EYE CONTACT:** Direct contact with dust may cause irritation by mechanical abrasion. Conjunctivitis may occur.

**SKIN CONTACT:** Direct contact may cause irritation by mechanical abrasion. Some components of material are also known to cause irritant effects to skin and mucous membranes.

**SKIN ABSORPTION:** Not expected to be a significant route of exposure.

**INGESTION:** Small amounts (a tablespoonful) swallowed during normal handling operations are not likely to cause injury. Ingestion of large amounts may cause gastrointestinal irritation and blockage.

**INHALATION:** Dust may irritate nose, throat, mucous membranes and respiratory tract by mechanical abrasion. Coughing, sneezing, chest pain, shortness of breath, inflammation of mucous membrane, and flu-like fever may occur following exposures in excess of appropriate exposure limits.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

Inhaling respirable dust and/or crystalline silica may aggravate existing respiratory system disease(s) (e.g., bronchitis, emphysema, chronic obstructive pulmonary disease) and/or dysfunctions. Exposure to dust may aggravate existing skin and/or eye conditions. Smoking and obstructive/restrictive lung diseases may also exacerbate the effects of excessive exposure to this product.

This product is a mixture of metal silicates and contains crystalline silica as one of its components. The composition percentages are listed in Section III. Toxicological information for each component is listed below:

**Metal Silicates (including mica):**

Exposure route: Inhalation, skin/eye contact.

Target organs: Eyes, skin, respiratory system.

Acute effect: Some of the silicate components are known to cause moderate irritation of the eyes, skin and respiratory system.

Chronic effect/carcinogenicity: The silicates typically contain quartz and the corresponding known health effects are listed in this section under silicon dioxide. Some of the silicate components have been reported to produce lung fibrosis and/or pneumoconiosis in the absence of crystalline silica. Not classifiable as human carcinogen.

**SECTION XI – TOXICOLOGICAL INFORMATION, CONTD.**

**Silicon Dioxide:** It is comprised of amorphous and crystalline forms of silica.

Exposure route: Eyes, respiratory system.

Target organs: Eyes, skin, respiratory system.

ACGIH, MSHA, and OSHA have determined that adverse effects are not likely to occur in the workplace provided exposure levels do not exceed the appropriate exposure limits. Lower exposure limits may be appropriate for some individuals including persons with pre-existing medical conditions as described under medical conditions aggravated by exposure.

**A. SILICOSIS**

The major concern is **silicosis** (lung disease), caused by the inhalation and retention of respirable crystalline silica dust. Silicosis leads to conditions such as lung fibrosis and reduced pulmonary function. The form and severity in which silicosis manifests itself, depends in part on the type and extent of exposure to silica dusts: chronic, accelerated and acute forms are recognized. In later stages the critical condition may become disabling and potentially fatal. Restrictive and/or obstructive changes in lung function may occur due to exposure. A risk associated with silicosis is development of pulmonary tuberculosis (silico-tuberculosis). Respiratory insufficiencies due to massive fibrosis and reduced pulmonary function, possibly with accompanying heart failure, are other potential causes of death due to silicosis.

Chronic or Ordinary Silicosis is the most common form of silicosis and can occur after many years of exposure to levels above the OELs for airborne respirable crystalline silica dust. Not all individuals with silicosis will exhibit symptoms (signs) of the disease. Symptoms of silicosis may include (but are not limited to): Shortness of breath; difficulty breathing with or without exertion; coughing; diminished work capacity; diminished chest expansion; reduction of lung volume; heart enlargement and/or failure. It is further defined as either simple or complicated silicosis.

Simple Silicosis is characterized by lung lesions (shown as radiographic opacities) less than 1 centimeter in diameter, primarily in the upper lung zones. Often, simple silicosis is not associated with symptoms, detectable changes in lung function or disability. Simple silicosis may be progressive and may develop into complicated silicosis or progressive massive fibrosis (PMF).

Complicated Silicosis or PMF is characterized by lung lesions (shown as radiographic opacities) greater than 1 centimeter in diameter. Although there may be no symptoms associated with complicated silicosis or PMF, the symptoms, if present, are shortness of breath, wheezing, cough and sputum production. Complicated silicosis or PMF may be associated with decreased lung function and may be disabling. Advanced complicated silicosis or PMF may lead to death. Advanced complicated silicosis or PMF can result in heart disease (cor pulmonale) secondary to the lung disease.

Accelerated Silicosis can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; the lung lesions can appear within five (5) years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that the lung lesions appear earlier and the progression is more rapid.

Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is a rapidly progressive, incurable lung disease and is typically fatal.

**B. CANCER**

IARC - The International Agency for Research on Cancer ("IARC") concluded that there is "*sufficient evidence* in humans for the carcinogenicity of crystalline silica in the form of quartz or cristobalite", there is "*sufficient evidence* in experimental animals for the carcinogenicity of quartz dust" and that there is "*limited evidence* in experimental animals for the carcinogenicity of tridymite dust and cristobalite dust." The overall IARC evaluation was that "crystalline silica inhaled in the form of quartz or cristobalite dust is *carcinogenic to humans (Group 1)*." The IARC evaluation noted that not all industrial circumstances studied evidenced carcinogenicity. The monograph also stated that "Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." For further information on the IARC evaluation, see IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Volume 100C, "Silica Dust, Crystalline, in the Form of Quartz or Cristobalite" (2012).

NTP - In its Eleventh Annual Report on Carcinogens, concluded that respirable crystalline silica is known to be a human carcinogen, based on sufficient evidence of carcinogenicity from studies in humans indicating a causal relationship between exposure to respirable crystalline silica and increased lung cancer rates in workers exposed to crystalline silica dust.

**SECTION XI – TOXICOLOGICAL INFORMATION, CONTD.**

OSHA - Crystalline silica is not on the OSHA carcinogen list.

CALIFORNIA PROPOSITION 65 - Crystalline silica in October 1996 was listed on the Safe Drinking Water and Toxic Enforcement ACT of 1986 as a chemical known to the state to cause cancer or reproductive toxicity.

**F. NON-MALIGNANT RESPIRATORY DISEASES**

NIOSH has cited the results of studies that report an association between dusts found in various mining operations and non-malignant respiratory disease, particularly among smokers, including bronchitis, emphysema, and small airways disease. *NIOSH Hazard Review – Health Effects of Occupational Exposure to Respirable Crystalline Silica*, published in April 2002, available from NIOSH, 4676 Columbia Parkway, Cincinnati, OH 45226, or at <http://www.cdc.gov/niosh/02-129A.html>.

Respirable dust containing newly broken particles has been shown to be more hazardous to animals in laboratory tests than respirable dust containing older silica particles of similar size. Respirable silica particles which had aged for sixty days or more showed less lung injury in animals than equal exposures of respirable dust containing newly broken pieces of silica.

Acute Toxicity Estimates for Feldspathic Sand - Unrefined – Not Available

**SECTION XII – ECOLOGICAL INFORMATION**

No data available for this product.

**SECTION XIII – DISPOSAL CONSIDERATIONS****WASTE DISPOSAL METHOD**

Collect and reuse clean materials. Dispose of waste materials only in accordance with applicable federal, state, and local laws and regulations.

The above information applies to Martin Marietta product only as sold. The product may be contaminated during use and it is the responsibility of the user to assess the appropriate disposal method in that situation.

**SECTION XIV – TRANSPORT INFORMATION****DOT HAZARD CLASSIFICATION**

None

**PLACARD REQUIRED**

None

**LABEL REQUIRED**

Label as required by the OSHA Hazard Communication standard {29 CFR 1910.1200(f)}, and applicable state and local regulations.



## SECTION XV – REGULATORY INFORMATION

**OSHA:** Crystalline Silica is not listed as a carcinogen.

**SARA Title III:** Section 311 and 312: Immediate health hazard and delayed health hazard.

**TSCA.:** Some components of the product appear on the EPA TSCA chemical substance inventory.

**RCRA:** This product is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR §261 *et seq.*

**CERCLA:** This product is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA), 40 CFR §302.4

**EPCRA (Emergency Planning and Community Right to Know Act):** This product is not an extremely hazardous substance under regulations of the **Emergency Planning and Community Right to Know Act, 40 CFR Part 355, Appendices A and B** and is not a toxic chemical subject to the requirements of Section 313.

**Clean Air Act:** Crystalline silica (quartz) mined and processed by Martin Marietta was not processed with or does not contain any Class I or Class II ozone depleting substances.

**FDA:** Silica is included in the list of substances that may be included in coatings used in food contact surfaces, 21 CFR §175.300(b)(3). (The FDA standard primarily applies to products containing silica used in the coatings of food contact surfaces).

**California Proposition 65: Respirable** crystalline silica (quartz) is classified as a substance known to the state of California to be a carcinogen.

## SECTION XVI – OTHER INFORMATION

### DEFINITIONS OF ACRONYMS/ABBREVIATIONS

ACGIH: American Conference of Governmental Industrial Hygienists

AL: Action Level

ANSI: American National Standards Institute

APF: Assigned Protection Factor

California REL: California Inhalation Reference Exposure Limit

CAS: Chemical Abstracts Service

CERCLA: Comprehensive Environmental Response, Compensation and Liability Act

CFR: US Code of Federal Regulations

DHHS: Department of Health and Human Services

EPA: Environmental Protection Agency

EPCRA: Emergency Planning and Community Right to Know Act

FDA: Food and Drug Administration

GHS: Globally Harmonized System

HEPA: High-Efficiency Particulate Air

IARC: International Agency for Research on Cancer

IDLH: Immediately Dangerous to Life and Health

MPPCF: Millions of Particles Per Cubic Foot

MSHA: Mine Safety and Health Administration

NIOSH: National Institute for Occupational Safety and Health, US Department of Health and Human Services

NIOSH REL: NIOSH Recommended Exposure Limit

NTP: National Toxicology Program

OEL: Occupational Exposure Limit

OSHA: Occupational Safety and Health Administration, US Department of Labor

PEL: Permissible Exposure Limit

PMF: Progressive Massive Fibrosis

RCRA: Resource Conservation and Recovery Act

SARA Title III: Title III of the Superfund Amendments and Reauthorization Act, 1986

SDS: Safety Data Sheet

STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value

TSCA: Toxic Substance Control Act

TWA: Time-Weighted Average

**SECTION XVI – OTHER INFORMATION, CONTD.**

User's Responsibility: The OSHA Hazard Communication Standard 29 CFR 1910.1200 requires that this SDS be made available to your employees who handle or may be exposed to this product. Educate and train your employees regarding applicable precautions. Instruct your employees to handle this product properly.

Disclaimer: The information contained in this document applies to this specific material as supplied and Martin Marietta believes that the information contained in this SDS is accurate. The suggested precautions and recommendations are based on recognized good work practices and experience as of the date of publication. They are not necessarily all-inclusive or fully adequate in every circumstance as not all use circumstances can be anticipated. It may not be valid for this material if it is used in combination with other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for one's own particular use. Since the actual use of the product described herein is beyond our control, Martin Marietta, assumes no liability arising out of the use of the product by others. Appropriate warnings and safe handling procedures should be provided to handlers and users. Also, the suggestions should not be confused with nor followed in violation of applicable laws, regulation, rules or insurance requirement. However, product must not be used in a manner which could result in harm.

An electronic version of this SDS is available at [www.martinmarietta.com](http://www.martinmarietta.com). More information on the effects of crystalline silica exposure may be obtained from OSHA (phone number: 1-800-321-OSHA; website: <http://www.osha.gov>) or from NIOSH (phone number: 1-800-35-NIOSH; website: <http://www.cdc.gov/niosh>).

DATE OF PREPARATION 6/2018

REPLACES 4/2017

NO WARRANTY, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE IS MADE