



Specification Sheet for:

Product Type: Dolomitic Quicklime
Product Name: Pebble

Dolomitic Quicklime - Pebble is distinguished by low ignition loss, low sulfur levels, good slaking rate and optimum sizing. This product is available in bulk for shipments by rail or truck (dump).

Typical Chemical Analysis

Calcium Oxide	58.5%
Magnesium Oxide	40.5%
Carbon Dioxide	0.50%
Silicon Dioxide	0.26%
Iron Oxide	0.17%
Aluminum Oxide	0.10%
Sulfur	0.010%
Loss on Ignition	0.75%

Typical Size Distribution

2" x 1/4"

Bulk Density 53.0 lbs/ft³

NOTICE:

THE INFORMATION CONTAINED HEREIN IS, THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE. ANY RECOMMENDATIONS OR SUGGESTIONS MADE ARE WITHOUT WARRANTY OR GUARANTEE OF RESULTS SINCE CONDITIONS OF HANDLING AND OF USE ARE BEYOND OUR CONTROL; WE THEREFORE, ASSUME NO LIABILITY FOR LOSS OR DAMAGE INCURRED BY FOLLOWING THESE SUGGESTIONS. SELLER WARRANTS ONLY THAT THIS PRODUCT WILL MEET THE SPECIFICATIONS SET FORTH. ANY OTHER REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, IS SPECIFICALLY DISCLAIMED INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY. SELLER'S MANUFACTURER'S ONLY OBLIGATION SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT PROVIDED TO BE DEFECTIVE. BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR USER'S INTENDED APPLICATION AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. NEITHER SELLER NOR MANUFACTURER SHALL BE LIABLE IN TORT, CONTRACT OR UNDER ANY THEORY FOR ANY LOSS OR DAMAGE, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR THE INABILITY TO USE THE PRODUCT.

Martin Marietta Magnesia Specialties LLC.
Woodville, OH
Phone: 419-849-4200
Fax: 419-849-4246